

TOUCHSCREENS

INFORMATION

21.5" DeepContrast PCAP+ 10pt touchscreen monitor featuring IPS panel technology, Edge-to-Edge glass design, anti-fingerprint and anti-glare coating



Enjoy smooth and intuitive control with the ProLite T2252MSC-W2AG, a 21.5" Full HD touchscreen built for natural and precise touch. Its DeepContrast PCAP+ (Optical Bonded PCAP) 10-point touch technology ensures instant responsiveness, vivid contrast and reduced reflections thanks to optical bonding, in addition, the display is protected from moisture and potential condensation development. The anti-fingerprint and anti-glare coating keeps the screen clean and easy to read, while the IPS panel delivers rich colours and consistent image quality from any angle.

Designed for comfort and efficiency, the adjustable stand supports ergonomic positioning, and the integrated cable management system keeps your workspace neat. With built-in audio and versatile connectivity (HDMI, DisplayPort, USB 3.2 hub), it offers a clean and flexible setup. Sleek edge-to-edge glass and a refined white design make it as stylish as it is functional – perfect for interactive signage, retail, POS, hospitality and creative spaces.



Vivid colors and wide viewing angles

Ensure perfect visibility from any position - The IPS panel delivers vivid, consistent colors and wide viewing angles, ideal for dynamic retail environments and busy commercial spaces.



Responsive interaction and good protection

Featuring intuitive DeepContrast PCAP+ touch technology with Optical Bonding, the screen offers smooth and responsive interaction with reduced glare, while remaining protected from moisture and condensation. Perfect for high-use environments.



Deep contrast and less reflections

Enjoy crystal-clear visuals with deep contrast and less glare - the optical bonded touch panel ensures sharp, easy-to-read content, even under bright retail lighting.



Always clear, always clean

The scratch-resistant, anti-fingerprint coating keeps the screen looking clear and professional even in busy retail settings, reducing visible smudges and protecting the surface from daily wear - your content always shines and the display stays easy to clean.

01 DISPLAY CHARACTERISTICS

Design	Edge to edge glass
Diagonal	21.5", 54.6cm
Panel	IPS
Native resolution	1920 x 1080 @100Hz (2.1 megapixel Full HD)
Aspect ratio	16:9
Panel brightness	250 cd/m ²
Brightness	215 cd/m ² with touch
Light transmittance	90%
Static contrast	1000:1 with touch
Response time (GTG)	5ms
Viewing zone	horizontal/vertical: horizontal/vertical 178°/178°
Colour support	16.7mln 8bit
Horizontal Sync	30 - 86kHz
Viewable area W x H	478.6 x 260mm, 18.8 x 10.2"
Pixel pitch	0.249mm
Bezel colour and finish	white, matte

02 TOUCH

Touch technology	optical bonding PCAP
Touch points	10 (HID, only with supported OS)
Touch method	stylus, finger, glove (latex)
Touch interface	USB
Supported operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Palm rejection	yes

03 INTERFACES / CONNECTORS / CONTROLS

Digital signal input	HDMI x1 DisplayPort x1
Audio output	Mini jack x1 Speakers 2 x 1W
HDCP	yes
USB HUB	x2 (USB 3.2 Gen 1 (5Gbps, 5V, 900mA))

04 FEATURES

Extra	DeepContrast PCAP+ (optical Bonding PCAP), anti-fingerprint, anti-glare coating, touch support with gloved hand (thickness +2mm)
-------	--

Glass hardness	7H
OSD key lock	yes

05 GENERAL

OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, NL, PL
Control buttons	Joystick: right/menu/enter, left/input/exit, up/eco, down, power
User controls	picture adjust (brightness, contrast, i-Style, adv. contrast, ECO, OD, X-Res technology), color settings (gamma, RGB range, color temp.), image settings (video mode adjust, blue light reducer, sharp & soft), OSD (horizontal position, vertical position, time, background), extra (reset, DCC/CI, signal select, volume, mute, opening logo, led, touch switch)
Convenience	Kensington-lock™ prepared
Blue light reducer	yes
Flicker free	yes
Plug&Play	DDC2B

06 MECHANICAL

Orientation	landscape, face-up
Tilt angle	90° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

07 ACCESSORIES INCLUDED

Cables	power (1.8m), USB (1.5m), HDMI (1.5m)
Guides	quick start guide, safety guide
Other	Screwdriver
Cable cover	yes

08 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, V, 50/60Hz
Power usage	13W typical, 0.5W stand by, 0.3W off mode

09 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH, UKCA, cTUVus
Energy efficiency class (Regulation (EU) 2017/1369)	D
REACH SVHC	above 0.1%: Lead, Lead monoxide (lead oxide)

10 DIMENSIONS / WEIGHT


Product dimensions 493.5 x 361.5 x 239.5mm
W x H x D

Box dimensions W x H x D 560 x 350 x 150mm

Weight (without box) 4.5kg

Weight (with box) 6kg

EAN code 4948570127191





All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED