

Passive HDMI cables

Model	Length	Max. Resolution	Ethernet / ARC	HDCP 2.2 / HDR10	HDMI K-lock Connector*	Con-ductors	Triple Shielding	O.D (mm)	Jacket Color	Rating / Compli-ance Standards	Special feature
C-HM/HM-3	3ft / 0.9m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	6.5 ± 0.15	Gray	CL3/FT4	Premium HDMI certified
C-HM/HM-6	6ft / 1.8m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	6.5 ± 0.16	Gray	CL3/FT4	Premium HDMI certified
C-HM/HM-10	10ft / 3.0m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	6.5 ± 0.17	Gray	CL3/FT4	Premium HDMI certified
C-HM/HM-15	15ft / 4.6m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	6.5 ± 0.18	Gray	CL3/FT4	Premium HDMI certified
C-HM/HM-25	25ft / 7.6m	4K@60Hz (4:2:0)	✓	✓	✓	28AWG	✓	6.5 ± 0.19	Gray	CL3/FT4	
C-HM/HM-35	35ft / 10.7m	4K@60Hz (4:2:0)	✓	✓	✓	28AWG	✓	6.5 ± 0.20	Gray	CL3/FT4	
C-HM/HM-50	50ft / 15.2m	1080p@60Hz	✓	✓	✓	26AWG	✓	9.0 ± 0.25	Gray	CL3/FT4	
C-MHM/MHM-1	1ft / 0.3m	4K@60Hz (4:4:4)	✓	✓	✓	30AWG	✓	5.8 ± 0.19	Gray	VW-1/FT4	Flexible
C-MHM/MHM-2	2ft / 0.6m	4K@60Hz (4:4:4)	✓	✓	✓	30AWG	✓	5.8 ± 0.19	Gray	VW-1/FT4	Flexible
C-MHM/MHM-3	3ft / 0.9m	4K@60Hz (4:4:4)	✓	✓	✓	30AWG	✓	5.8 ± 0.19	Gray	VW-1/FT4	Flexible
C-MHM/MHM-6	6ft / 1.8m	4K@60Hz (4:4:4)	✓	✓	✓	30AWG	✓	5.8 ± 0.19	Gray	VW-1/FT4	Flexible
C-MHM/MHM-10	10ft / 3.0m	4K@60Hz (4:4:4)	✓	✓	✓	30AWG	✓	5.8 ± 0.19	Gray	VW-1/FT4	Flexible
C-MHM/MHM-15	15ft / 4.6m	1080p@60Hz 12-bit	✓	✓	✓	30AWG	✓	5.8 ± 0.19	Gray	VW-1/FT4	Flexible
C-MHM/MHM-25	25ft / 7.6m	1080p@60Hz	✓	✓	✓	30AWG	✓	5.8 ± 0.19	Gray	VW-1/FT4	Flexible
C-MHM/MHM-35	35ft / 10.7m	1080p@60Hz	✓	✓	✓	30AWG	✓	5.8 ± 0.19	Gray	VW-1/FT4	Flexible
C-HM/HM/PRO-3	3ft / 0.9m	4K@60Hz (4:4:4)	✓	✓	✓	26AWG	✓	8 ± 0.19	Black	CL3/FT4	Premium HDMI certified
C-HM/HM/PRO-6	6ft / 1.8m	4K@60Hz (4:4:4)	✓	✓	✓	26AWG	✓	8 ± 0.19	Black	CL3/FT4	Premium HDMI certified
C-HM/HM/PRO-10	10ft / 3.0m	4K@60Hz (4:4:4)	✓	✓	✓	26AWG	✓	8 ± 0.19	Black	CL3/FT4	Premium HDMI certified
C-HM/HM/PRO-15	15ft / 4.6m	4K@60Hz (4:4:4)	✓	✓	✓	26AWG	✓	8 ± 0.19	Black	CL3/FT4	Premium HDMI certified
C-HM/HM/PRO-20	20ft / 6.1m	4K@60Hz (4:4:4)	✓	✓	✓	24AWG	✓	8 ± 0.19	Black	CL3/FT4	Premium HDMI certified
C-HM/HM/PRO-25	25ft / 7.6m	4K@60Hz (4:2:0)	✓	✓	✓	26AWG	✓	8 ± 0.19	Black	CL3/FT4	Best resolution/length ratio
C-HM/HM/PRO-35	35ft / 10.7m	4K@60Hz (4:2:0)	✓	✓	✓	26AWG	✓	8 ± 0.19	Black	CL3/FT4	Best resolution/length ratio
C-HM/HM/PRO-50	50ft / 15.2m	1080p@60Hz 12-bit	✓	✓	✓	24AWG	✓	9.5 ± 0.25	Black	CL3/FT4	Best resolution/length ratio
C-HM/HM/PRO-65	65ft / 19.5m	1080p@60Hz	✓	✓	✓	24AWG	✓	9.5 ± 0.25	Black	CL3/FT4	Best resolution/length ratio
C-HM/ETH-3	3ft / 0.9m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	7.3 ± 0.15	Gray	CL3/FT4	cost effective entry level
C-HM/ETH-6	6ft / 1.8m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	7.3 ± 0.16	Gray	CL3/FT4	cost effective entry level
C-HM/ETH-10	10ft / 3.0m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	7.3 ± 0.17	Gray	CL3/FT4	cost effective entry level
C-HM/ETH-15	15ft / 4.6m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	7.3 ± 0.18	Gray	CL3/FT4	cost effective entry level
C-HM/ETH-25	25ft / 7.6m	4K@60Hz (4:2:0)	✓	✓	✓	28AWG	✓	7.3 ± 0.19	Gray	CL3/FT4	cost effective entry level
C-HM/ETH-35	35ft / 10.7m	4K@60Hz (4:2:0)	✓	✓	✓	28AWG	✓	7.3 ± 0.20	Gray	CL3/FT4	cost effective entry level
C-HM/ETH-50	50ft / 15.2m	1080p@60Hz	✓	✓	✓	26AWG	✓	8.5 ± 0.25	Gray	CL3/FT4	cost effective entry level
C-HMU-3	3ft / 0.9m	8k@60	✓	✓	✓	30AWG	✓	6 ± 015	Black	CL3/FT4	Ultra HDMI certified 8K@60
C-HMU-6	6ft / 1.8m	8k@60	✓	✓	✓	30AWG	✓	6 ± 015	Black	CL3/FT4	Ultra HDMI certified 8K@60
C-HMU-10	10ft / 3.0m	8k@60	✓	✓	✓	28AWG	✓	7 ± 015	Black	CL3/FT4	Ultra HDMI certified 8K@60
C-HMU-15	15ft / 4.6m	8k@60	✓	✓	✓	26AWG	✓	8.5 ± 0.15	Black	CL3/FT4	Ultra HDMI certified 8K@60
C-HM/HM/FLAT/ETH-3	3ft / 0.9m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	3.0x12.6	Black	CL3/FT4	Flat cable
C-HM/HM/FLAT/ETH-6	6ft / 1.8m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	3.0x12.6	Black	CL3/FT4	Flat cable
C-HM/HM/FLAT/ETH-10	10ft / 3.0m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	3.0x12.6	Black	CL3/FT4	Flat cable
C-HM/HM/FLAT/ETH-15	15ft / 4.6m	4K@60Hz (4:2:0)	✓	✓	✓	26AWG	✓	3.8x16.8	Black	CL3/FT4	Flat cable
C-HM/HM/FLAT/ETH-25	25ft / 7.6m	4K@60Hz (4:2:0)	✓	✓	✓	26AWG	✓	3.8x16.8	Black	CL3/FT4	Flat cable
C-HM/HM/FLAT/ETH-35	35ft / 10.7m	4K@60Hz (4:2:0)	✓	✓	✓	26AWG	✓	3.8x16.8	Black	CL3/FT4	Flat cable
C-HM/HM/FLAT/ETH-50	50ft / 15.2m	1080p@60Hz 12-bit	✓	✓	✓	24AWG	✓	4.2x18.3	Black	CL3/FT4	Flat cable
C-HM/HM/FLAT/ETH-75	75ft / 22.9m	1080p@60Hz	✓	✓	✓	24AWG	✓	4.2x18.4	Black	CL3/FT4	Flat cable
C-HM/HM/PICO-1	1ft / 0.3m	4K@60Hz (4:4:4)	✓	✓	—	34AWG	—	3.6 ± 0.15	Various*	VW-1	Slim Colored cable *
C-HM/HM/PICO-2	2ft / 0.6m	4K@60Hz (4:4:4)	✓	✓	—	34AWG	—	3.6 ± 0.15	Various*	VW-1	Slim Colored cable *
C-HM/HM/PICO-3	3ft / 0.9m	4K@60Hz (4:4:4)	✓	✓	—	34AWG	—	3.6 ± 0.15	Various*	VW-1	Slim Colored cable *
C-HM/HM/PICO-6	6ft / 1.8m	4K@60Hz (4:4:4)	✓	✓	—	34AWG	—	3.6 ± 0.15	Various*	VW-1	Slim Colored cable *
C-HM/HM/PICO-10	10ft / 3.0m	4K@60Hz (4:2:0)	✓	✓	—	34AWG	—	3.6 ± 0.15	Various*	VW-1	Slim Colored cable *
CLS-HM/HM/ETH-3	3ft / 0.9m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	8.0 ± 0.19	Gray	IEC 60332-1 & IEC 60754-1	LSHF flame rate
CLS-HM/HM/ETH-6	6ft / 1.8m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	8.0 ± 0.19	Gray	IEC 60332-1 & IEC 60754-1	LSHF flame rate
CLS-HM/HM/ETH-10	10ft / 3.0m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	8.0 ± 0.19	Gray	IEC 60332-1 & IEC 60754-1	LSHF flame rate
CLS-HM/HM/ETH-15	15ft / 4.6m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	8.0 ± 0.19	Gray	IEC 60332-1 & IEC 60754-1	LSHF flame rate
CLS-HM/HM/ETH-25	25ft / 7.6m	4K@60Hz (4:2:0)	✓	✓	✓	28AWG	✓	8.0 ± 0.19	Gray	IEC 60332-1 & IEC 60754-1	LSHF flame rate
CLS-HM/HM/ETH-35	35ft / 10.7m	4K@60Hz (4:2:0)	✓	✓	✓	28AWG	✓	8.0 ± 0.19	Gray	IEC 60332-1 & IEC 60754-1	LSHF flame rate
CLS-HM/HM/ETH-50	50ft / 15.2m	1080p@60Hz	✓	✓	✓	26AWG	✓	9.0 ± 0.25	Gray	IEC 60332-1 & IEC 60754-1	LSHF flame rate
CP-HM/HM/ETH-15	15ft / 4.6m	4K@60Hz (4:4:4)	✓	✓	✓	24AWG	✓	10.5 ± 0.20	Black	CMP	Plenum flame rate
CP-HM/HM/ETH-25	25ft / 7.6m	4K@60Hz (4:2:0)	✓	✓	✓	24AWG	✓	10.5 ± 0.21	Black	CMP	Plenum flame rate
CP-HM/HM/ETH-35	35ft / 10.7m	4K@60Hz (4:2:0)	✓	✓	✓	24AWG	✓	10.5 ± 0.22	Black	CMP	Plenum flame rate
CP-HM/HM/ETH-40	40ft / 12.0m	4K@60Hz (4:2:0)	✓	✓	✓	24AWG	✓	10.5 ± 0.23	Black	CMP	Plenum flame rate
CP-HM/HM/ETH-45	45ft / 13.7m	4K@60Hz (4:2:0)	✓	✓	✓	24AWG	✓	10.5 ± 0.24	Black	CMP	Plenum flame rate
CP-HM/HM/ETH-50	50ft / 15.2m	1080p@60Hz 12-bit	✓	✓	✓	24AWG	✓	10.5 ± 0.25	Black	CMP	Plenum flame rate

* Black, Blue, Green, White

Active HDMI cable

Model	Length	Max. Resolution	Ethernet / ARC	HDCP 2.2 / HDR10	HDMI K-lock Connector*	Conductors	Triple Shielding	O.D (mm)	Jacket Color	Rating / Compliance Standards	Special feature
CA-HM-15	15ft / 5m	4K@60Hz (4:4:4)	✓	✓	✓	32AWG	✓	5.5 ± 0.20	Gray	CL3/FT4	Cooper wires with Active chipset on the far end
CA-HM-25	25ft / 7.0m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	7.1 ± 0.30	Gray	CL3/FT4	Cooper wires with Active chipset on the far end
CA-HM-35	35ft / 10.0m	4K@60Hz (4:4:4)	✓	✓	✓	28AWG	✓	7.1 ± 0.30	Gray	CL3/FT4	Cooper wires with Active chipset on the far end
CA-HM-50	50ft / 15.0m	4K@60Hz (4:4:4)	✓	✓	✓	26AWG	✓	8.5 ± 0.30	Gray	CL3/FT4	Cooper wires with Active chipset on the far end
CA-HM-66	66ft / 20m	4K@60Hz (4:4:4)	✓	✓	✓	24AWG	✓	9.5 ± 0.30	Gray	CL3/FT4	Cooper wires with Active chipset on the far end
CA-HM-82	82ft / 25m	4K@60Hz (4:2:0)	✓	✓	✓	24AWG	✓	9.5 ± 0.30	Gray	CL3/FT4	Cooper wires with Active chipset on the far end
CA-HM-98	98ft / 30m	1080p@60Hz	✓	✓	✓	24AWG	✓	9.5 ± 0.30	Gray	CL3/FT4	Cooper wires with Active chipset on the far end

AOC HDMI cables

Model	Length	Max. Resolution	Ethernet / ARC	HDCP 2.2 / HDR10	HDMI K-lock Connector*	Conductors	Triple Shielding	O.D (mm)	Jacket Color	Rating / Compliance Standards	Special feature
CLS-AOCH/60-33-328	33-328ft / 10-100m	4K@60Hz (4:4:4)	—	✓	✓	NA	NA	3.4 ± 0.20	Black	LSHF	Active Optic Cable, pluggable connector
CP-AOCH/60-33-328	33-328ft / 10-100m	4K@60Hz (4:4:4)	—	✓	✓	NA	NA	3.4 ± 0.20	Black	CMP	Active Optic Cable, pluggable connector
CLS-AOCH/60F-33-295	33-328ft / 10-90m	4K@60Hz (4:4:4)	—	✓	✓	NA	NA	4.5 ± 0.20	Black	LSHF	Active Optic Cable, Fixed connector
CP-AOCH/60F-33-295	33-328ft / 10-90m	4K@60Hz (4:4:4)	—	✓	✓	NA	NA	4.5 ± 0.20	Black	CMP	Active Optic Cable, Fixed connector
CLS-AOCH/UF-33-328	33-328ft / 10-100m	8K@60	—	✓	✓	NA	NA	4.5 ± 0.20	Black	LSHF	Active Optic Cable, 8K@60 Fixed connector
CP-AOCH/UF-33-328	33-328ft / 10-100m	8K@60	—	✓	✓	NA	NA	4.5 ± 0.20	Black	CMP	Active Optic Cable, 8K@60 Fixed connector
CRS-FIBERH-SI-6-164	6-164ft / 1.8-50m	4K@60Hz (4:2:0)	—	✓	✓	NA	NA	3.4 ± 0.20	Black	—	Active Optic Cable, pluggable connector Uni directional
CRS-PlugNview-H-33-328	33-328ft / 10-100m	4K@60Hz (4:4:4)	—	✓	✓	NA	NA	5.8 ± 0.20	Black	LSHF	Active Optical Armored 4K HDMI Cable Extremely Durable
CP-AOCH/PF	33-328ft / 10-100m	4K@60Hz (4:4:4)	—	✓	✓	NA	NA	4 ± 0.3	Black	CMP	Pure fiber Optical Armored 4K HDMI Cable