



MC3-2Hi

4K60 HDMI 2xIN Card

| HDMI | 4K/60 UHD (4:4:4)



MC3-2Hi is a high-performance two-port HDMI input card which is part of the compatible modular matrices multi-signal cards family. MC3-2Hi can flexibly occupy any of the matrix card slots and its input signals are independently switched by the modular matrix to any of the matrix output ports

FEATURES

High Resolution Audio-Visual Experience - Modular matrix input card supports high 4K60 4:4:4 AV signal distribution towards any output port of the modular matrix

HDMI™ Signal Distribution - HDCP 2.2 compliant, supporting deep color, x.v.Color™, CEC, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified by the HDMI 2.0 standard

Multi-channel Audio Transmission - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound



TECHNICAL SPECIFICATIONS

Inputs	2 HDMI: On female HDMI connectors
Video	Max Data Rate: 18Gbps (6Gbps per graphics channel) Max Resolution: 4K@60Hz (4:4:4) HDMI Support: HDR 10, 3D, Deep Color, x.v.Color™, ARC, Dolby® TrueHD, Dolby Digital Plus, DTS-HD®, and 7.1 multi-channel audio Content Protection: HDCP 2.2/1.4 compliant
Power	Consumption 5W
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
Regulatory Compliance (Standards Compliance)	Safety: CE
Product Dimensions	12.90cm x 24.90cm x 2.00cm (5.08" x 9.80" x 0.79") W, D, H
Product Weight	0.2kg (0.5lbs) approx
Shipping Dimensions	29.20cm x 16.50cm x 6.00cm (11.50" x 6.50" x 2.36") W, D, H
Shipping Weight	0.4kg (0.9lbs) approx

