



VS-44H2A

4x4 4K HDR HDMI HDCP 2.2 Matrix Switcher
with Audio De-embedding

| HDMI | Ethernet - RJ-45 | 4K/60 UHD (4:4:4)



VS-44H2A is a high-performance 4x4 matrix switcher for 18G 4K@60Hz (4:4:4) HDR HDMI signals. It reclocks and equalizes the signals and can route any one of four HDMI, HDCP-compliant sources (selectable) to any or all outputs simultaneously

FEATURES

High-Performance AV Matrix - Switches 4 4K@60Hz (4:4:4) HDR HDMI HDCP-compliant signals to 4 18G 4K@60Hz (4:4:4) HDR HDMI HDCP-compliant outputs at up to 18G data rate. Signals are HDCP 2.2/1.4 compliant, supporting HDR10, xvYCC color, Dolby TrueHD/DTS-HD Master Audio, 3D Video as specified in HDMI 2.0

Analog and Digital Audio De-embedding (Extraction) - De-embeds the audio signal and outputs it as balanced analog audio with separate volume control on each of the outputs and S/PDIF digital audio

Easy Step-In Collaboration Function - When used with a Kramer Step-In enabled switcher, just plug in your device and press the Step-In button. Your device becomes the active signal on the main display

Features Kramer Equalization & reKlocking™ Technology - Rebuilds the digital signal to travel longer distances

EDID Management - Individual EDID management per input. Captures and stores the EDID from a display device

Flexible Content Protection - Selectable HDCP per input

Quick Access to Common Configurations - Save up to four preset configurations and recall them using front panel buttons

Convenient Unit Control and Configuration Options - Local control via front panel switching, memory, lock and EDID buttons, Input/Output LED display. Distance control via user-friendly embedded web pages via the Ethernet, Protocol 3000 API, and RS-232 serial commands transmitted by a PC, touch screen system or other serial controller

Cost-Effective Maintenance - IR and Input Selection indicators facilitate easy local maintenance and troubleshooting. Firmware upgrade via Ethernet or USB using a user-friendly software upgrade tool

Easy Installation - 19" enclosure for rack mounting a unit in a 1U rack space with included rack ears and universal 100-240V AC power connection



TECHNICAL SPECIFICATIONS

Inputs	4 HDMI: On female HDMI connectors
Outputs	4 HDMI: On female HDMI connectors 4 S/PDIF: On female RCA connectors 4 Balanced Stereo Audio: On 5-pin terminal block connectors
Ports	1 USB: On a Mini female connector 1 RS-232: On a 9-pin D-sub connector 1 IR IN: On a 3.5mm mini jack 1 Ethernet: On an RJ-45 female connector
Video	Max. Resolution: 4K@60Hz 4:4:4 Max. Data Rate: 18Gbps (6Gbps per graphic channel) Content Protection Supports HDCP 2.2/1.4 HDMI Support HDR10, xvYCC color, Dolby TrueHD/DTS-HD Master Audio, 3D Video as specified in HDMI 2.0
User Interface	Front Panel: IN and OUT selection buttons; OFF, ALL, STO, RCL EDID, LOCK buttons
Power	Source: 100–240V AC, 50/60Hz Consumption: 60VA
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: –40° to +70°C (–40° to 158°F) Humidity: 10% to 90%, RH non-condensing
STANDARDS COMPLIANCE	Safety: CE Environmental: RoHs, WEEE
Enclosure	Size: 19" 1U Type Aluminum Cooling: Fan
Accessories	Included: Power cord, rack ears
Product Dimensions	43.64cm x 18.30cm x 4.36cm (17.18" x 7.20" x 1.72") W, D, H 43.64cm x 23.72cm x 4.36cm (17.18" x 9.34" x 1.72") W, D, H
Product Weight	2.0kg (4.5lbs) approx 2.0kg (4.5lbs) approx
Shipping Dimensions	55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H 52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H
Shipping Weight	2.9kg (6.5lbs) approx

2.9kg (6.5lbs) approx

